



# uptown I

# Upholstery Leather

## Grade 1



801 Rally Black

---

## Grade 2

### Spinneybeck Verona



VR 946 Dark Gray



VR 906 Midnight



VR 910 Thicket



VR 979 Butter



VR 8029 Caramel



VR 2010 Ruby



VR 900 Black



VR 908 Claret

For the complete Spinneybeck collection,  
please refer to the Commercial Price List.

Spinneybeck

1•800•482•7777 for larger samples.

# Upholstery Leather

## Grade 3

Spinneybeck Volo



VO 939 Talc




VO 901 Butterscotch



VO 940 Doeskin



VO 944 Sand



VO 965 Shaker Ochre



VO 945 Tan



VO 903 Toast



VO 947 Coffee Bean



VO 957 Oatmeal



VO 968 Fumo Oscuro



VO 971 Bistro




VO 969 Mammoth Cave



VO 910 Laurel



VO 955 Marine Blue



VO 973 Ocean Deep



VO 982 Kilim



VO 900 Black



VO 937 Claret

## Grade 5

Spinneybeck Andes/Velluto Pelle  
An additional 100 colors are available  
in this quality.

For the complete Spinneybeck collection,  
please refer to the Commercial Price List.



AD 6021 Gaucho

Spinneybeck

1•800•482•7777 for larger samples.

# Upholstery Leather

## Technical Data


### Spinneybeck Leather

### Standard Leather

<b>Verona (VR)</b>	<b>Volo (VO)</b>	<b>Andes/Velluto Pelle (AD/VP)</b>	<b>Rally Black</b>
A corrected, aniline dyed leather with a durable, breathable protective finish.	A lightly corrected, aniline dyed leather with a durable, breathable protective finish.	A smooth, lightly enhanced, aniline dyed leather with a durable, breathable protective finish.	A top grain, semi-aniline leather at an economical price point.
<i>Raw Material:</i> Northern Italian hides	<i>Raw Material:</i> Northern Italian hides	<i>Raw Material:</i> Northern Italian hides	<i>Raw Material:</i> Domestic hides
<i>Hide Size:</i> 55 sq. ft.	<i>Hide Size:</i> 50-55 sq. ft.	<i>Hide Size:</i> 50-55 sq. ft.	<i>Hide Size:</i> 47 sq. ft. (average size)
<i>Thickness:</i> 1.1 mm	<i>Thickness:</i> 1.1 mm	<i>Thickness:</i> 1.0 mm	<i>Thickness:</i> 0.9-1.1 mm
<i>Light Fastness:</i> Class 4 (AATCC Method 16, Option E, 72 hrs.)	<i>Light Fastness:</i> Class 4 (AATCC Method 16, Option E, 72 hrs.)	<i>Light Fastness:</i> Class 4 (AATCC Method 16, Option E, 72 hrs.)	<i>Flammability:</i> Cal Tech Bulletin 117
<i>Crocking:</i> Dry: Class 4-5 Wet: Class 4 (ASTM D-5053)	<i>Crocking:</i> Dry: Class 4-5 Wet: Class 4 (ASTM D-5053)	<i>Crocking:</i> Dry: Class 4-5 Wet: Class 4 (ASTM D-5053)	
<i>Abrasion:</i> 2,500+ cycles (ASTM D-3884)	<i>Abrasion:</i> 2,000+ cycles (ASTM D-3884)	<i>Abrasion:</i> 1,500+ cycles (ASTM D-3884)	
<i>Flammability:</i> Cal Tech Bulletin 117 Boston Fire Dept. BFD IX-1 Cigarette Ignition NFPA-260	<i>Flammability:</i> Cal Tech Bulletin 117 Boston Fire Dept. BFD IX-1 Cigarette Ignition NFPA-260	<i>Flammability:</i> Cal Tech Bulletin 117 Boston Fire Dept. BFD IX-1 Cigarette Ignition NFPA-260	

### Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap. Do not soak. Never clean with abrasive solvents, alcohol or wax-based products. Approved maintenance products are available from Spinneybeck.



6415 Katella Avenue  
Cypress, CA 90630

☎ (888) 274-8664  
☎ (714) 995-4855

🌐 www.sitonit.net  
✉ sales@sitonit.net

Form No. C307-1 2/04 15M

# Spinneybeck

1 • 8 0 0 • 4 8 2 • 7 7 7 7 for larger samples.